



631 Rust Preventative

DESCRIPTION

Rustlick 631 is a moisture-displacing rust preventative and corrosion inhibitor designed for long-term in-door use. It spreads into scratches and pores to displace moisture and leaves an oily thin-film. 631 is easily applied and removed, non-conductive, and safe to use on electrical parts.

FEATURES

- Displaces moisture and water
- Easy aerosol spray application
- No chlorinated solvents
- Non-conductive

APPLICATIONS

- For corrosion and rust prevention
- Spray on wherever protection is needed

DIRECTIONS

Aerosol: Spray on wherever protection is needed, Bulk: Apply by brushing or dipping

HANDLING

Aerosol: Keep away from heat, sparks and open flame. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Bulk: Keep away from heat, sparks and open flame. No smoking. Use only in area provided with appropriate exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Wear personal protective equipment. Wash thoroughly after handling.

STORAGE

Aerosol: Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Bulk: Keep away from open flames, hot surfaces and sources of ignition. Keep container tightly closed in a dry and well-ventilated place.

DISPOSAL

Aerosol: This material, as supplied, is not a hazardous waste according to Federal regulations (40CFR 261). Bulk: This material, as supplied, is not a hazardous waste according to Federal regulations (40CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.



PROPERTIES

Appearance / Physical State	Liquid
Odor	Characteristic
Melting / Freezing Point	No data available
Boiling Point / Range	Aerosol: No data available Bulk: 100°C / 212°F
Vapor Pressure	No data available
Partition Coefficient	No data available
Percent volatile	No data available
Flammability	No data available
Propellant	Aerosol: Propane Bulk: N/A
VOC Content	72%
Color	Brown
Flash Point	Aerosol: -156°F (-104°C) Bulk: 180°F (82°C)
Density	6.8 lbs/gal
Evaporation Rate	<1
Vapor density	>1
Auto-Ignition Temperature	No data available
Viscosity	No data available
Specific Gravity	0.82
Temperature Range	No data available
4-Ball Weld Load	No data available

SHELF LIFE INFORMATION

2 years



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved



631 Rust Preventative

AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Approximate Case Weight
71011	1 gal	container	4	30 lbs
71051	5 gal	pail	1	36 lbs
71551	55 gal	drum	1	410 lbs



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved