



# BFX

## All-Purpose Cleaner



### FEATURES

- Industrial strength for hard to remove soils and oils
- Water-based and biodegradable for safer cleaning alternative
- Ideal for parts washers and pressure washers
- Safe to use on most surfaces except for magnesium
- Non-corrosive formula to inhibit flash rusting
- Does not contain butyl or phosphates

### APPLICATIONS

- Aluminum
- Carbon
- Carpet
- Chrome
- Counters
- Diesel Fuel
- Dip Tanks
- Floor Scrubbers
- Machinery
- Painted Surfaces
- Parts Washers
- Pressure Sprayers
- Smoke
- Soot
- Spot Cleaning
- Vents

### SPECIFICATIONS AND APPROVALS

- NSF International, C1

### PROPERTIES

Appearance / Physical State	Liquid
Odor	Sassafras
Melting / Freezing Point	32°F (0°C)
Boiling Point / Range	212°F (100°C)
Vapor Pressure	17.5 mm Hg @ 20°C
Partition Coefficient	Not available
Percent volatile	99%
Flammability	Not available
Propellant	Not available
VOC Content	0% per US State & Federal Consumer Product Regulations
Color	Light yellow
Flash Point	None
Density	Not available
Evaporation Rate	1 BuAc
Vapor density	>1
Auto-Ignition Temperature	Not available
Viscosity	1 cST@ 20°C
Specific Gravity	1.02
Temperature Range	Not available
4-Ball Weld Load	Not applicable

### DIRECTIONS

(Trigger) Turn nozzle to spray or stream position. Pull trigger to spray. (Bulk) KEEP FROM FREEZING. MIX WELL BEFORE USING. Rinse and/or wipe dry any residue. Test for compatibility on delicate materials.

Dilution Ratio Product:

Water Equipment Applications

1: 4 Parts Washers Carbon blocks, engines, exhaust hoods, forklifts, graffiti, marine, tanks, varnish

1: 5 Dip Tanks Aviation, compressors, food processing equipment, floors, hoists, lifts, printing presses, tools

1: 7 Tumblers Drill presses, oily parts, pulleys and wires

1: 10 Ultrasonic Cleaning electrical parts (Deionized water rinse/dry)

1: 4-20 Steam Cleaner Engines, parts

1: 60 Trigger Sprayer Floors, leather and fabrics, tile, walls, wood

1: 40-80 Pressure Washer Cleaning parts, floors, trucks, etc.

1: 100 Trigger Sprayer Appliances, formica, general cleaning of glass, walls

### HANDLING

Avoid prolonged exposure. Observe good industrial hygiene practices.

### STORAGE

Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS)

### DISPOSAL

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose in accordance with all applicable regulations.

### AVAILABLE PRODUCTS

Part No.		Net Contents	Container Type	Units/Case	Approximate Case Weight
US	Canada				
05528	C05528	28 fl oz / 828 mL	trigger	12	27 lbs
05501		1 gal / 3.78 L	bottle	4	37 lbs
05555	C05555	55 gal / 208 L	drum	1	535 lbs



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | [www.itwprobrands.com](http://www.itwprobrands.com)

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved