



# FG-2000

## Foodgrade High Performance Metal Cutting Fluid

### FEATURES

- Moderate to heavy-duty
- Vegetable-based, biodegradable lubricant
- For ferrous & nonferrous metals, aluminum and titanium
- Clean before heat treating with soap and water

### APPLICATIONS

- General machining, sawing and cutting
- Food-grade applications
- Medical device manufacturing
- Swiss style CNC machining centers
- Milling, drilling and tapping

### HANDLING

Avoid contact with skin, eyes, clothing. Wash thoroughly after handling.

### STORAGE

Keep container tightly closed in a dry and well-ventilated place.

### SPECIFICATIONS AND APPROVALS

- NSF International, H1 #162799



### PHYSICAL PROPERTIES

|                             |                   |
|-----------------------------|-------------------|
| Appearance / Physical State | Liquid            |
| Odor                        | Mild              |
| Specific Gravity            | 0.92              |
| Flash Point                 | >204 °C / >400 °F |
| Boiling Point / Range       | >204 °C / >400 °F |
| Vapor Pressure              | <1 mmHg           |
| VOC Content                 | 0.2 g/L           |
| Vapor Density               | >1                |
| Prop 65 Warning             | NO                |

### AVAILABLE PRODUCTS

| Part No. | Net Contents | Container Type | Units/Case | Color |
|----------|--------------|----------------|------------|-------|
| FG2001   | 1 gal        | bottle         | 4          | gold  |
| FG2055   | 55 gal       | drum           | 1          | gold  |



**CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!**

800.241.8334 | [www.itwprobrands.com](http://www.itwprobrands.com)

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved