



# Food Grade Machine & Penetrating Oil



## FEATURES

- Metal detectable plastic components-DETEX®
- Penetrates to loosen frozen nuts and bolts
- Colorless, non-staining lubricant
- Eliminates sticking, binding, and squeaking
- Provides excellent lubricity
- Safe on most surfaces

## APPLICATIONS

- Castors
- Chains
- Channels
- Conveyors
- Filling Equipment
- Food Racks
- Food Service Carts
- Slicers

## SPECIFICATIONS AND APPROVALS

- Canadian Food Processors
- Meets FDA Regulation 21 C.F.R. 178.3570 for incidental food contact
- NSF® Certified: H1

## PROPERTIES

Appearance / Physical State	Clear Liquid
Odor	Slight Petroleum Odor
Melting / Freezing Point	Not available
Boiling Point / Range	> 435.2°F (> 224°C)
Vapor Pressure	< 0.05 mm Hg @ 20°C
Partition Coefficient	< 1
Percent volatile	0.6
Flammability	Lower: 0.6%, Upper: 7%
Propellant	Carbon Dioxide
VOC Content	0% per U.S. State and Federal Consumer Product Regulations
Color	Clear. Colorless.
Flash Point	> 158.0°F (> 70.0°C) Tag Closed Cup
Density	Not available
Evaporation Rate	< 0.1 BuAc
Vapor density	4.7
Auto-Ignition Temperature	> 442.4°F (> 228°C)
Viscosity	Viscosity 130 - 160 cP
Specific Gravity	0.81 - 0.83 @ 20°C
Temperature Range	0°F (-17°C) to 385°F (196°C)
4-Ball Weld Load	Not available

## DIRECTIONS

Shake well before using. Apply on clean surface. Hold can 10-12 inches away from surface and spray evenly. If desired, attach extension tube for difficult to reach areas. Wipe off excess. Reapply as needed. Do not add directly to food. Use only in well ventilated areas. Avoid all sources of ignition (spark or flame).

## HANDLING

Pressurized container: Do not pierce or burn, even after use. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Avoid prolonged or repeated contact with skin. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

## STORAGE

Keep container in a cool, well-ventilated area. Avoid all sources of ignition (spark or flame). Store below 120°F. Store aerosols as Level 3 Aerosol (NFPA 30B). Store all materials in dry, well-ventilated area. Avoid breathing vapors.

## DISPOSAL

Waste must be disposed of in accordance with national, regional, provincial, and local environmental control regulations.

## AVAILABLE PRODUCTS

Part No.		Net Contents	Container Type	Units/Case	Approximate Case Weight
US	Canada				
01316	C01316	11 wt oz / 312 g / 376 mL	aerosol	12	12 lbs



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | [www.itwprobrands.com](http://www.itwprobrands.com)

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved