



G-49

Orange Degreaser Low VOCs



FEATURES

- Reduced VOCs (Volatile Organic Compounds)
- Conforms to the VOC regulations of CARB (California Air Resources Board), OTC (Ozone Transport Commission) and LADCO (Lake Michigan Air Directors Consortium)
- Instant cleaning action, no residue
- Excellent for removing grease, grime, oil, and adhesives
- High solvent strength
- Moderate evaporation
- Excellent alternative to Methyl Ethyl Ketone (MEK)
- Not a Hazardous Air Pollutant (HAP)
- No ozone depleting compounds (ODC)
- Inverta SprayValve can be sprayed at almost any angle

APPLICATIONS

- Bearings
- Chains
- Controls
- De-energized Cable Connections
- Forklifts
- Gears
- Hand & Power Tools
- Heavy Equipment
- Instruments
- Machinery
- Motors
- Pulleys

SPECIFICATIONS AND APPROVALS

- NSF International, C1

PROPERTIES

| | |
|------------------------------------|---|
| Appearance / Physical State | Gas/Aerosol |
| Odor | Acetone/Orange |
| Percent volatile | 100% |
| Flammability | Flammability limit - lower (%) 2.5% Flammability limit - upper (%) 12.8% |
| Propellant | Carbon dioxide |
| VOC Content | 9.45% per US State and Federal Consumer Product Regulations |
| Color | Clear water-white |
| Flash Point | -4.0 °F (-20.0 °C) Tag Closed Cup (estimated) |
| Density | Not available |
| Evaporation Rate | 0.2 BuAc |
| Viscosity | Not available |
| Specific Gravity | 0.81 @ 20°C |

DIRECTIONS

Apply on parts and equipment. Allow solvent to dissolve and remove contaminants. Air dry or wipe with an absorbent cloth for faster drying. If equipment is still dirty or greasy, repeat procedure.

HANDLING

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. (See Section 7 of the SDS)

STORAGE

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Keep away from heat and sources of ignition. (See Section 7 of the SDS)

DISPOSAL

Consult authorities before disposal. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.

AVAILABLE PRODUCTS

| Part No. | | Net Contents | Container Type | Units/Case | Approximate Case Weight |
|----------|--------|---------------------------|----------------|------------|-------------------------|
| US | Canada | | | | |
| 06420 | C06420 | 15 wt oz / 425 g / 528 mL | aerosol | 12 | 15 lbs |



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved