

Accu-Lube® LB-6000

Light Viscosity MQL

FEATURES

- Moderate to heavy-duty
- Vegetable-based, biodegradable lubricant
- Non-staining, burns off cleanly in post heat treating
- Clean with soap and water

APPLICATIONS

- Aluminum machining, cutting and sawing
- Aluminum applications with post-heat treating
- Moderate-duty milling, drilling, tapping and punching

DIRECTIONS

Fill Accu-Lube applicator reservoir above the low-level line. Refer to the Accu-Lube applicator manual for operating instructions.

HANDLING

Avoid contact with skin, eyes and clothing. Wash thoroughly after handling.

STORAGE

Store at 10-49°C / 50-120°F. Keep container tightly closed.

DISPOSAL INFORMATION

Consult the appropriate state, regional, or local regulations for additional requirements.



PHYSICAL PROPERTIES

Appearance/physical state	Liquid
Odor	Mild
Melting point/freezing point	No data available
Boiling point/range	>200°C
Vapor pressure	No data available
Partition coefficient	No data available
Percent volatile	No data available
Flammability limit	No data available
VOC Content	No data available
Color	Blue
Flash point	>200°C
Relative density	No data available
Evaporation rate	No data available
Vapor density	No data available
Auto-ignition temperature	No data available
Viscosity	No data available
Specific Gravity (water=1)	0.93
Temperature Range °F(°C)	No data available
4-Ball Weld Load	No data available

AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Case Weight
LB6000	1 gal	jug	4	34 lbs
LB6055	55 gal	drum	1	454 lbs



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved