



LPS[®] MAX Heavy-Duty Silicone Water-Based Lubricant & Protectant



FEATURES

- Eliminates binding/provides runner & plastic parts protection
- Locking flip straw actuator
- Long term, water-based, silicone lubricant
- Provides protection for rubber and plastic parts
- Safe on metals
- No chlorinated solvents or other harsh chemicals
- Non-petroleum lubricant
- Nozzle provides targeted or broad stroke application
- Embossed can for improved hand grip

APPLICATIONS

- Cables
- Castors
- Moving Plastic Parts
- O-rings
- Plastic Gears
- Plastic Rollers
- Rubber Brushings
- Seals
- Sprockets
- Valves
- Ignition Systems
- Relays

SPECIFICATIONS AND APPROVALS

- Central Power & Light
- City Public Service
- General Motors Co.
- Kimberly-Clark
- Kodak
- New York City Transit
- NSF International: H1

AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Case Weight
91516	13 wt oz / 369 g / 439 mL	aerosol	12	12 lbs

HANDLING

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Close valve after each use and when empty. Protect cylinders from physical damage; do not drag, roll, slide, or drop. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Suck back of water into the container must be prevented. Do not allow backfeed into the container. Purge air from system before introducing gas. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

STORAGE

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Keep away from heat, sparks and open flame. This material can accumulate static charge which may cause spark and become an ignition source. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in original tightly closed container. Store in a well-ventilated place. Cylinders should be stored upright, with valve protection cap in place, and firmly secured to prevent falling or being knocked over. Stored containers should be periodically checked for general condition and leakage.

DISPOSAL

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS[®], SCRUBS[®], DYKEM[®], Accu-Lube[®], DYMON[®], Spray Nine[®], and Cedar[®] are registered trademarks and Rustlick[™], Diamondkote[™], and MetalMates[™] are trademarks of Illinois Tool Works • All Rights Reserved