



# OVS 280-20

## Stamping Lubricant

OVS 280 is a thinner viscoisty OVS designed for stamping, piercing, and punching.

### FEATURES

- Extends tool life
- Will not build up in dies
- Can be welded without wash
- Can be diluted in wide range
- Thin viscosity

### APPLICATIONS

- Spray, brush, roll coat or drip. Good on multiple substrates, please call for consultation on specific applications.

### DIRECTIONS

Dilute Metal Mates OVS with water to suit the specific application.

NOTE: These dilution ratios should only be used as general guidelines and are not exact specifications. Please contact your Metal Mates Regional Sales Manager for an application specific recommendation. Slowly add water to lubricant while mixing. Water quality enhances the performance of all water-dilutable lubricants.

### HANDLING

Use appropriate safety equipment. Use with adequate ventilation. Avoid contact with eyes, skin and clothing. Keep away from extreme heat. Keep container closed when not in use.

### DISPOSAL

Absorb on suitable material and follow procedures listed below. Dispose of in a manner that is recommended by local, state, provincial and federal laws and regulations.



### PROPERTIES

<b>Odor</b>	mild
<b>pH Value</b>	8.3-9.3
<b>Specific Gravity</b>	0.98
<b>Flash Point</b>	>200F (>93C)
<b>Boiling Point / Range</b>	212F (100C)
<b>Vapor Pressure</b>	<1
<b>Vapor Density</b>	Heavier than air
<b>Prop 65 Warning</b>	Yes
<b>Dilution Ratio</b>	Typical Dilution: 3:1 to 6:1 (33-17%)
<b>Melting / Freezing Point</b>	212F (100C)
<b>Total Chlorine</b>	Y

### AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case
MM2103	55 gal	drum	1
MM2106	330 gal	tote	1



**CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!**

800.241.8334 | [www.itwprobrands.com](http://www.itwprobrands.com)

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved