

Accu-Lube® Stick Lube

Hand-Applied Lubricant

FEATURES

- Lubricant stick for rotating or stationary cutting tools
- Reduces heat build-up
- Vegetable-based

APPLICATIONS

- Short-run machining
- Rotating or stationary cutting tools
- Belt, disc and wheel grinding
- Ferrous & nonferrous metals, aluminum and titanium

DIRECTIONS

Apply sparingly, directly on the tool.

HANDLING

Avoid contact with skin, eyes and clothing. Wash thoroughly after handling.

STORAGE

Keep container tightly closed in a dry and well-ventilated place.

DISPOSAL

Dispose of in accordance with local regulations.



PHYSICAL PROPERTIES

Appearance / Physical State	Solid
Odor	Mild
Melting / Freezing Point	110-120°F/43-49°C
Boiling Point / Range	> 400°F/>204°C
Vapor Pressure	< 1 mmHg
Partition Coefficient	No data available
Percent volatile	No data available
Flammability	No data available
Propellant	N/A
VOC Content	None
Color	White
Flash Point	> 200°F/>93°C
Density	No data available
Evaporation Rate	No data available
Vapor density	>1
Auto-Ignition Temperature	No data available
Viscosity	No data available
Specific Gravity	0.86
Temperature Range	No data available
4-Ball Weld Load	No data available

AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Approximate Case Weight
79042	2.2 oz	push-up stick	24	6 lbs
79045	13 wt oz	Stick	24	23 lbs



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved