

Accu-Lube® Synthetic General Purpose MQL

FEATURES

- Replacement for straight oil
- Multi-purpose
- Water-based, synthetic lubricant
- Cools like flood coolant, lubricates like straight oil
- Rapid heat dissipation
- Clean before heat treating with rinse water

APPLICATIONS

- General machining, sawing and cutting
- For ferrous metals

DIRECTIONS

Fill Accu-Lube applicator reservoir above the low-level line. Refer to the Accu-Lube applicator manual for operating instructions.

HANDLING

Do not get in eyes. Wear eye protection/ face protection

STORAGE

Keep containers tightly closed in a dry, cool and well-ventilated place.

DISPOSAL INFORMATION

Dispose of in accordance with local regulations.



PHYSICAL PROPERTIES

Appearance/physical state	Liquid
Odor	Mild
Melting point/freezing point	No data available
Boiling point/range	>100°C
Vapor pressure	No data available
Partition coefficient	No data available
Percent volatile	No data available
Flammability limit	No data available
Propellant	N/A
VOC Content	No data available
Color	Blue
Flash point	>100°C
Relative density	No data available
Evaporation rate	No data available
Vapor density	No data available
Auto-ignition temperature	No data available
Viscosity	No data available
Specific Gravity (water=1)	1.04
Temperature Range °F(°C)	No data available
4-Ball Weld Load	No data available

AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Case Weight
LBSYNT01	1 gal	bottle	4	36 lbs
LBSYNT55	55 gal	drum	1	499 lbs



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved