



VS 160-30 Stamping Lube

Metal Mates VS-160-30 is a medium duty lubricant for stamping, piercing and punching.

FEATURES

- Universal for wide range of parts
- Easily cleaned weld without wash

APPLICATIONS

- Spray, brush, roll coat or drip. Good on multiple substrates, please call for consultation on specific applications.

DIRECTIONS

Dilute Metal Mates VS with water to suit the specific application. Slowly add water to lubricant while mixing. Water quality enhances the performance of all water-dilutable lubricants.

HANDLING

Use appropriate safety equipment. Use with adequate ventilation. Avoid contact with eyes, skin and clothing. Keep away from extreme heat. Keep container closed when not in use.

DISPOSAL

Absorb on suitable material and follow procedures listed below. Dispose of in a manner that is recommended by local, state, provincial and federal laws and regulations.



PROPERTIES

Odor	mild
pH Value	8.0-9.0
Specific Gravity	0.99
Flash Point	>200F (>93C)
Boiling Point / Range	212F (100C)
Melting / Freezing Point	212F (100C)
Vapor Pressure	<1
Vapor Density	Heavier than air
Prop 65 Warning	Yes
Total Chlorine	Y
Dilution Ratio	Typical Dilution 3:1 to 6:1 (33-17%)

AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Color
MM1002	5 gal	pail	1	creamy white
MM1003	55 gal	drum	1	creamy white
MM1006	330 gal	tote	1	creamy white



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved